

PermaLift® Marine Lift Tanks Sizes



PermaLift™ Lift Tank Sizes

| Marine Lift Tanks | Length (in) | Width (in) | Height (in) | Volume (ft³) | Wall Thickness 0.350" | | Wall Thickness 0.375" | |
|---|----------------|---------------|----------------|-----------------|--------------------------|------------------|--------------------------|------------------|
| | | | | | Weight (lb) | Buoyancy (lb) | Weight (lb) | Buoyancy (lb) |
| Standard Marine Lift Tank - 30" depth | 96 | 34 | 30 | 49.2 | 183 | 2890 | 196 | 2877 |
| Standard Marine Lift Tank - 36" depth | 96 | 34 | 36 | 60.1 | 211 | 3540 | 226 | 3525 |
| Shallow Water Marine Lift Tank | 168 | 32 | 24 | 73.2 | 245 | 4326 | 262 | 4309 |

**1961 Rockdale Industrial
Blvd. Conyers, GA 30012**

**400 E Houser Ave
Sallisaw, OK 74955**



800-468-3626



www.cellofoam.com



@rotomarineproducts

*All weights, buoyancies, and dimensions are nominal and subject to manufacturing tolerances. Buoyancy numbers provided are maximum assuming complete submersion. Lower buoyancies will be achieved with less than complete submersion. Purchasers of our floats and lift tanks should engage with professional design experts to incorporate these products into their marine systems.